



PURE cool DOOR SL

Refrigerated cabinet design for wall multidecks with frameless sliding doors made of insulated glass optional: PURE cool DOOR SL T with T-Edge

Energy efficiency with glass and light





Produktline

Multidecks

Frameless sliding doors

Hight

Deep / Front

PURE cool

DOOR

SL / SL T

ca. 2020 mm | ca. 2220 mm

ca. 783 mm / ca. 300 mm

Description

- The glass doors are made of a high-quality ISO composite consisting of 2x4 mm tempered glass and a 14 mm thick insulating layer filled with air or alternatively with argon gas. On request we can also supply our insulating glass doors as a 4-layer anti-reflective variant (residual reflection < 1%).
- The side panels consist of frameless 3-layer insulating glass made of high-quality tempered laminated safety glass.
- The frameless doors without thermal bridges can be individually adjusted with a tolerance range of up to +/- 5° in the angle of inclination.
- Even greater transparency is provided by top glass elements as presentation surfaces for backlit displays.
- The new LED lighting concept allows a wide range of lighting options for optimal merchandise presentation.
LED lighting elements can be optionally integrated:
 - vertically on the inside panels behind the glass surfaces
 - horizontally on the display shelves
 - horizontally as decorative lighting in the top glass element and base section
 - horizontally in the lower guide profile



Produktline

Multidecks

Frameless sliding doors

Hight

Deep / Front

PURE cool

DOOR

SL / SL T

ca. 2020 mm | ca. 2220 mm

ca. 783 mm / ca. 300 mm

Optional with T-Edge – Innovation from PAN-DUR

Visually transparent composite for insulating glass

Further plus points

- The doors run on sliding rails integrated into the base section. The top section of the unit is thus not subjected to any static loads. This makes vertical supports unnecessary.
- The opening and closing function is situated on an inclined plane.
- No easily damaged cable guides, rollers or weights.
- An optimal opening dimension at the top, together with a low loading sill, allows optimal filling and removal of merchandise.
- The durable and virtually maintenance-free ball bearing supported slide surfaces in the base section are installed out of sight. Nothing disturbs the elegant glass appearance.
- The upper glass guide profile lies within a coated aluminum double U profile.
- The door opening mechanism has soft stops and an integrated magnetic holding function when the door is open.
- Easy, hygienic cleaning of the glass surfaces.

Produktline

Multidecks

Frameless sliding doors

Hight

Deep / Front

PURE cool

DOOR

SL / SL T

ca. 2020 mm | ca. 2220 mm

ca. 783 mm / ca. 300 mm

